

AS07A2VA AS09A2VA/AS12A2VC AQ09A2VA/AQ12A2VC

7,500~11,500 BTU Single High Wall Air Conditioner


- Heatpump • New Slim-line Design • Turbo Cooling • High Energy Efficiency Ratio
- Low Noise Level • Air Purifying System • Sleep Operation • Auto Air Swing
- 24hr On/Off Timer/Off Timer • New LCD Remote Controller • Washable Grille




AS07A2VA AS09A2VA/AS12A2VC AQ09A2VA/AQ12A2VC

7,500~11,500 BTU Single High Wall Air Conditioner

Indoor Dimension



Outdoor Dimension



KEY FEATURES

- Heatpump
- New Slim-line Design
- Turbo Cooling
- High Energy Efficiency Ratio
- Low Noise Level
- Air Purifying System
- Sleep Operation
- Auto Air Swing
- 24hr On/Off Timer/Off Timer
- New LCD Remote Controller
- Washable Grille
- Auto Restart

SINGLE SPECIFICATIONS

Model			AS07A2VA	AS09A2VA	AS12A2VC	AQ09A2VA	AQ12A2VC	
Voltage / Hz			115V / 60Hz	115V / 60Hz	208-230V / 60Hz	115V / 60Hz	208-230V / 60Hz	
Performance	Capacity	Cooling	BTU/Hr	7,500	9,000	11,500	9,000	11,500
			WATT	2,198	2,637	3,517	2,637	3,517
	Heating		BTU	-	-	-	9,500	12,500
			WATT	-	-	-	2,784	3,663
	SEER	Cooling		10.0	10.0	10.	10.0	10.0
	HSPF			-	-	-	7.0	6.8
	Dehumidifying Capacity		Pts/Hr	1.9	2.3	3.0	2.3	3.0
Air Circulation(At High Speed CFM)		ft ³ /min	176.6	211.9	275.5	215.4	275.5	
Sound Level (H1650)	(In/Out)	dB	36 / 45	38 / 47	39 / 50	38 / 48	45 / 51	
Power	Running Current	Cooling	A	6.3	8.3	5.8	8.5	6.0
		Heating	A	-	-	-	8.2	6.4
	Maximum Branch Circuit Fuse	A	15	15	15	15	15	
	Power Input	Cooling	WATT	670	880	1,280	900	1,280
Heating		WATT	-	-	-	880	1,430	
Size	Net Weight	Inddor	lbs	21.2	21.2	21.2	21.2	21.2
		Outdoor	lbs	59.5	59.5	59.5	59.5	70.5
	ShippingWeight	Indoor	lbs	24.9	24.9	24.9	24.9	70.5
		Outdoor	lbs	68.3	68.3	75.0	70.5	77.2
	Line Set Size	Liquid Line	Inch	1/4	1/4	1/4	1/4	1/4
		Suction Line	Inch	3/8	3/8	1/2	3/8	1/2
	Net Dimension (Indoor)	W x D x H	Inch	32 3/16 x 7 3/16 x 11 3/16	32 3/16 x 7 3/16 x 11 3/16	32 3/16 x 7 3/16 x 11 3/16	32 3/16 x 7 3/16 x 11 3/16	32 3/16 x 7 3/16 x 11 3/16
		(Outdoor)	Inch	28 3/16 x 9 3/16 x 20 3/16	28 3/16 x 9 3/16 x 20 3/16	28 3/16 x 9 3/16 x 20 3/16	28 3/16 x 9 3/16 x 20 3/16	28 3/16 x 9 3/16 x 20 3/16
	Shipping Dimension (Indoor)	W x D x H	Inch	34 3/16 x 9 3/16 x 14 3/16	34 3/16 x 9 3/16 x 14 3/16	34 3/16 x 9 3/16 x 14 3/16	34 3/16 x 9 3/16 x 14 3/16	34 3/16 x 9 3/16 x 14 3/16
		(Outdoor)	Inch	33 3/16 x 12 3/16 x 22 3/16	33 3/16 x 12 3/16 x 22 3/16	33 3/16 x 12 3/16 x 22 3/16	33 3/16 x 12 3/16 x 22 3/16	33 3/16 x 12 3/16 x 22 3/16
Loading Q'ty	W / O Pipe	20 / 40	116 / 252	116 / 252	116 / 252	116 / 252	116 / 252	
	W Pipe	20 / 40	113 / 243	113 / 243	113 / 243	113 / 243	113 / 243	

* Design and specifications are subject to change without notice.



SAMSUNG AIR CONDITIONING
2865 Pellissier Place Whittier, CA 90601
TEL: (562) 463-0880 Fax: (562) 463-5665
Toll Free: (888) 463-0880
www.samsung-ac.com